LEVITON

Arc 90 LED Lighting Fixture

DESCRIPTION

The Arc 90 takes color mixing to the next level with 90 3W LEDs, making this fixture extremely powerful for both indoor and outdoor applications. The LED configuration allows the creation of pastel shades or pure white color washing.

- (90) 3W LEDs
- Three LED Packages to fit any application:
  - RGBW - Red (18), Green (24), Blue (24), White (24)
  - RGBA - Red (18) Green (24) Blue (24), Amber (24)
  - WWA - White (48), Warm White (24), Amber (18)
- Vary the concentration of light with the field angle* that meets your specifications:
  - 15°
  - 30°
- Color mixing allows for pastels
- Control Options
  - DMX 512
  - Programmable up to 255 steps each color with “Stand Alone”
- Operating Modes
  - Master/Slave

INTERNAL PROGRAMS

- Color Snap - Scrolls the LEDs from one color to another from slow to fast, speed settings from 0-15
- Pre-Program Mode - Activate 15 pre-stored programs
- Chase Mode - Activate 15 Chase pre-stored programs
- Macros
  - Color Fade
  - Color Snap
  - Random
  - Color Fade RGB
  - Color Snap RGB
  - Pulse - Red, Green, Blue, White, Purple, Yellow, Aqua, All on Pulse, White LED Full
- Digital Display
- Dual Mounting Yoke
- IP65 Rated for Outdoor Use
- IP65 Rated Fan Cooling System
- US Assembled

* Field angles can vary +/- 5°

Leviton Mfg. Co., Inc. Lighting & Energy Solutions

20497 SW Teton Avenue, Tualatin, OR 97062 1-800-736-6682 Tech Line: 1-800-959-6004 Fax: 503-404-5594 www.glynaxorvema.live/les

© 2012 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

LEVITON

Arc 90 LED Lighting Fixture

SPECIFICATIONS

PHYSICAL	
Size	14.25" x 10.5" x 15.5" (36.195cm x 26.67cm x 39.37cm)
Weight	26 lbs (11.79 kg)
ELECTRICAL	
DMX Connectors	3-Pin XLR Connectors with weather seal
Voltage	110V, 50Hz
Max Wattage	246 Watts/3.08 Amps
LED Lifetime	60,000-100,000 hours
ENVIRONMENTAL	
IP	65

NOTE: Included accessories: NEMA 5-15P, Parallel Blade & Ground Plug, 15A

ARC 90 LED LIGHTING ORDERING KEY

L A □ □ □ - 0 P □

LED PACKAGE

2 = RGBW

3 = RGBA

6 = WWA

FIELD ANGLE

15 = 15°

30 = 30°

HOUSING COLOR

B = Black

A = Aluminum

ORDERING INFORMATION

CAT. NO.	DESCRIPTION
TA0CC-000	C-Clamp
TA0SC-000	Safety Cable

LEVITON SPECIFICATION SUBMITTAL	
JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc. Lighting & Energy Solutions
20497 SW Teton Avenue, Tualatin, OR 97062 Å Tel: 1-800-736-6682 Å Fax: 503-404-5594 Å Tech Line (6:00AM-4:00PM P.S.T. Mon-Fri): 1-800-959-6004

Leviton Manufacturing Co., Inc. Global Headquarters
201 N. Service Rd. Melville, NY 11747-3138 Å Tech Line: 1-800-824-3005 Å Fax: 1-800-832-9538

Leviton Manufacturing of Canada, Ltd.
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 Å Telephone: 1-800-469-7890 Å FAX: 1-800-563-1853

Leviton S. de R.L. de C.V.
Lago Tana 43, Mexico DF, Mexico CP 11290 Å Tel. (+52) 55-5082-1040 Å FAX: (+52) 5386-1797 Å www.leviton.com.mx

Visit our Website at: www.gylnaxorvema.live/les

© 2012 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.